

ExamcollectionPass

Pass Your Next Certification Exam Fast!

Login / Register

Shopping Cart (3)

Everything you need to prepare, learn & pass your certification exam easily.

Search...



Online Test Engine

Instant Online Access, Test History and Performance Review, Supports Windows / Mac / Android / iOS, etc. →

Desktop Test Engine

Installable Software Application, Simulates Real Exam Environment, Supports MS Operating System, Practice Offline Anytime. →

PDF Format

Printable PDF Format, Prepared by IT Experts, Study Anywhere, Anytime, Free PDF Demo Available. →

Download a free pdf sample of any of our study materials

- ▶ 24/7 customer support, Secure shopping site
- ▶ Free One year updates to match real exam scenarios
- ▶ If you failed your exam after buying our products we will refund the full amount back to you.

Select a vendor... ▼

Select an test... ▼

Your email address

Free Download Demo



48923+
Happy Clients



48923+
Shares



97846+
Downloads



9999+
Years in Business

<http://www.examcollectionpass.com/>

Everything you need to prepare, learn & pass your certification exam easily.

Exam : **JN0-105**

Title : Junos, Associate (JNCIA-Junos)

Vendor : Juniper

Version : DEMO

NO.1 Which two statements about firewall filters are correct? (Choose two.)

- A. Firewall filters are stateless.
- B. Firewall filters can match Layer 7 parameters.
- C. Firewall filters are stateful.
- D. Firewall filters can match Layer 4 parameters.

Answer: A D

Explanation:

Firewall filters in Junos OS are stateless, meaning they process each packet individually without regard to the state of a connection or sequence of packets. These filters can match various packet attributes, including those at Layer 4, such as TCP and UDP port numbers. This allows for granular control over traffic based on the type of service or application. Unlike stateless filters, stateful firewalls keep track of the state of active connections and make decisions based on the context of the traffic flow, which is not a capability of Junos firewall filters.

Additionally, Junos firewall filters primarily operate up to Layer 4 and do not natively inspect Layer 7 parameters, which involve application-level data.

NO.2 Click the Exhibit button.

Exhibit
✕

```

R2> ping 10.23.0.3
PING 10.23.0.3 (10.23.0.3): 56 data bytes
64 bytes from 10.23.0.3: icmp_seq=0 ttl=64 time=2.654 ms
64 bytes from 10.23.0.3: icmp_seq=1 ttl=64 time=2.673 ms
64 bytes from 10.23.0.3: icmp_seq=2 ttl=64 time=2.229 ms
^C
--- 10.23.0.3 ping statistics ---
3 packets transmitted, 3 packets received, 0% packet loss
round-trip min/avg/max/stddev = 2.229/2.519/2.673/0.205 ms
    
```

Referring to the exhibit, what is the source IP address of the ping that was executed?

- A. 10.12.0.2
- B. 10.23.0.2
- C. 10.23.0.3
- D. 10.24.0.4

Answer: B

Explanation:

The exhibit shows a ping test being executed from router R2 to the IP address 10.23.0.3. Since the ping command is issued on R2 and we see successful replies from 10.23.0.3, it means the source of the ping must be an interface on R2. Given the network diagram and the IP address scheme, the source IP address of the ping is on the interface ge-0/0/2 of R2, which is in the subnet 10.23.0.0/24. The only logical IP address for R2's interface in this subnet, based on standard networking practices and the given options, would be 10.23.0.2. The other addresses provided in the options belong to different subnets or are the destination of the ping itself.

NO.3 What will the request system configuration rescue save command do?

- A.** It saves the most recently committed configuration as the rescue configuration.
- B.** It saves the candidate configuration as the rescue configuration.
- C.** It saves a configuration version prior to the configuration most recently committed as the rescue configuration.
- D.** It activates the rescue configuration.

Answer: A

Explanation:

The request system configuration rescue save command in Junos OS saves the most recently committed configuration as the rescue configuration. This rescue configuration can be used to recover the device if future configurations cause issues. It ensures there is a stable, known-good configuration to fall back on, which is crucial in network management and troubleshooting.

References:

"rescue : save configurations as the rescue: request system configuration save(saves the current configs as a rescue configs)" from Useful Juniper Commands.txt.

Juniper official documentation: Configuring and Activating a Rescue Configuration.

NO.4 Which two statements describe the result when you enter? at the command-line prompt? (Choose two.)

- A.** It lists the available commands and options.
- B.** It lists tips for the help menu.
- C.** It displays help about a text string contained in a statement.
- D.** It displays summary information about the commands and options.

Answer: A D

Explanation:

When you enter ? at the command-line prompt in Junos OS, the system provides assistance in two significant ways. Firstly, it lists the available commands and options that can be used at the current point in the command hierarchy, aiding users in understanding what commands they can execute next. Secondly, it displays summary information about those commands and options, providing brief descriptions or additional context that can help users understand the function of each command or option. This feature is particularly useful for learning the command structure or for quick reference when specific command syntax is forgotten.

NO.5 What are two functions of the Routing Engine? (Choose two.)

- A. It processes all management traffic.
- B. It runs the Junos operating system.
- C. It evaluates firewall filters for transit traffic.
- D. It processes transit traffic.

Answer: A B

Explanation:

The Routing Engine (RE) in Junos OS has several critical functions, including processing all management traffic (A) and running the Junos operating system (B). The RE handles system management tasks, user interfaces, system services, and routing protocol processes. It does not directly process transit traffic or evaluate firewall filters for transit traffic, as these tasks are handled by the Packet Forwarding Engine (PFE).

NO.6 What does the `user@router> clear log ospf-trace` command accomplish?

- A. Logging data into ospf-trace is stopped.
- B. Trace parameters are removed from the OSPF protocol configuration.
- C. Data in the ospf-trace file is removed and logging continues.
- D. The ospf-trace file is deleted.

Answer: C

Explanation:

The `clear log ospf-trace` command on a Juniper Networks router is used specifically to manage the contents of the log file named `ospf-trace`. Executing this command clears or deletes the existing data within the `ospf-trace` log file but does not stop the logging process. The router continues to log new OSPF-related events and data into this file after the command is executed. This functionality is crucial for troubleshooting and monitoring the OSPF (Open Shortest Path First) protocol's operation by allowing network administrators to remove old or irrelevant log data while continuously capturing new events without interruption.

NO.7 Which two statements are true about the Junos OS? (Choose two.)

- A. Routing tables are stored in the control plane.
- B. Exception traffic is never sent to the control plane.
- C. Exception traffic is sent to the control plane.
- D. Routing tables are stored in the forwarding plane.

Answer: A C

Explanation:

In Junos OS, as with many network operating systems, the control plane is responsible for processes that determine how to route traffic. This includes maintaining routing tables, which store information about network paths and protocols. Therefore, routing tables are indeed stored in the control plane. Exception traffic refers to packets that cannot be processed by the normal fast-path processing of the Packet Forwarding Engine (PFE) in the forwarding plane, and thus are sent to the control plane for further processing. This might include packets destined for the router itself, packets that need to be fragmented, or packets that match certain firewall filter criteria, among other reasons.

Routing tables are not stored in the forwarding plane. However, the forwarding plane contains the forwarding table (sometimes referred to as the forwarding information base or FIB), which is a distilled version of the routing table optimized for fast packet forwarding. The forwarding plane uses this information to perform the actual transfer of packets across the network device interfaces.

NO.8 Which component is considered part of the data plane?

- A. the Routing Engine
- B. the Packet Forwarding Engine
- C. the fan tray
- D. the power supply

Answer: B

Explanation:

The Packet Forwarding Engine (PFE) is an integral component of Juniper Networks devices, responsible for the data plane operations. The data plane, also known as the forwarding plane, is where the actual processing and forwarding of packets occur based on the routing and forwarding tables. The PFE executes the forwarding decisions made by the Routing Engine (RE), handling all packet transmissions, including routing, filtering, and switching packets towards their destination. This contrasts with the control plane operations handled by the RE, which involve routing table maintenance, system management, and control protocol processing.

NO.9 How many login classes are assignable to a user account?

- A. 3
- B. 2
- C. 4
- D. 1

Answer: D

Explanation:

<https://www.juniper.net/documentation/us/en/software/junos/user-access-evo/user-access/topics/topic-map>

/junos-os-login-

class.html#:~:text=You%20can%20define%20any%20number,to%20an%20individual%20user%20account.

In Junos OS, each user account can be assigned only one login class. Login classes in Junos OS define the permissions for users, controlling what they can access and modify within the system. This setup helps in maintaining a clear and secure access control mechanism.

Reference:

Junos OS Documentation on User Accounts and Login Classes.

NO.10 After the factory default configuration is loaded, which configuration object must be created prior to the first commit?

- A. root authentication
- B. loopback IP address
- C. out-of-band connectivity
- D. host name

Answer: A

Explanation:

In Juniper Networks devices, when the factory default configuration is loaded, the first step before committing any configuration is to set up root authentication. This is crucial because it secures the device by ensuring that only authorized users have administrative access. Without setting up a root

password, the device will not allow any commit operations, which is a safety measure to prevent unauthorized access. This requirement emphasizes the importance Juniper places on security right from the initial setup of the device.

NO.11 Which two common routing policy actions affect the flow of policy evaluation? (Choose two.)

- A. next policy
- B. community
- C. next term
- D. next hop

Answer: A C

Explanation:

In Junos OS routing policy evaluation, "next policy" (A) and "next term" (C) are common actions that affect the flow of policy evaluation. "Next policy" directs the evaluation to the next policy in the sequence, whereas

"next term" moves the evaluation to the next term within the current policy, allowing for granular control over routing decisions.